






Product information

- Heavy duty cord operated system, with separate internal cord channels; preventing cord sag and eliminating cord tangle.
- Bendable; it can be curved and reversed curved with a 20 cm (8") radius or continuous curve.
- Heavy duty klickable carriers 10 carriers on a breakaway strip - UV protected.
- Can also be used for Forest Easyfold and accordiafold drapery systems.
- Maximum fabric weight: 8 kg. per mtr (5,3 LBS per ft).
- Colours available: white, silver.
- Track finish: chromated powder coating with a factory applied patented dry lubricant.
- Lengths available: 3.66 m (12'), 4.27 m (14'), 4.88 m (16'), 6.10 m (20').

Profile


- Shown actual size 1:1
- Aluminium Extrusion
- Weight: 300 gram per mtr (3.22 ounce per ft)
- Dimensions: 20 mm x 20 mm (3/4" x 3/4")



For use in

Hotels - motels - offices - healthcare - schools - residential or any location where a heavy duty cord traverse system is required.

Applications



Bending/curving

The track can be curved and reversed curved using a 20 cm (8") radius. Continuous curving can be done with the electric powered bender or by special order from factory.





		m Wall Bracket , powder coated.	10	203cm
		7,5 cm single 10 cm single 15 cm double 20 cm double 25 cm triple	(3") (4") (6") (8") (10")	20/box 20/box 15/box 15/box 10/box
	Colours: 0 ²	1, 03.		

CS/CCS/FMS Bending Wheel	2561000000 1/each
CCS Bending Strips	8500000002

Contract Bending tool For CS/CCS/FMS/CRS/MTS

For CCS track, length: 90 cm (35,4")	1/set
For CCS electric powered bender. Length 7 meter (23').	8500000010 1/each



1/each



В	ending Wheels	2560700000
Fo	r Electric Powered Bender.	1/set
C	omplete set of 3 wheels.	



Distributor:

2560000000 1/each

